

Type: Model: With lid: round bucket 11-1200 BIS P-10Bis/4

DIMENSIONS/WEIGHT

Upper diameter (inside): 273,3 mm (b)
Upper diameter (with flange): 290,0 mm (a)
Upper diameter (with handles): 289,8 mm
Bottom diameter (external): 252,0 mm (c)


Height (with standard lid): 259,5 mm (h)

Height (with lid for foiling):

Nominal capacity: 12 000 ml Total capacity: 13 840 ml Total usable capacity: 13 200 ml

Container weight: 362,0 g
Handle weight (strap): 14,5 g (standard)
Handle weight (PP): 20,0 g (optional)
Handle weight (metal): 34-44 g (optional)


Weight tolerance: +/- 5%
Dimension tolerance: +/- 1 mm





DECORATION

	Dry offset (up to 6 colors)	IML
Width (B):	830 mm	835,9 mm
Height (H):	180 mm	210,5 mm



LIDS

Name: P-10Bis/4
Foiling: No
Foiling: 90 g
IML: Yes
Offset: No



RAW MATERIAL / TRANSPORT AND WAREHOUSING

- Buckets and lids are made of polypropylene (PP)
- Warehousing: In the case of stacking pallets with filled containers put weight uniformly, using for example proper separators.
- Filling and closing conditions: max. content temperature during filling 95°C, during stacking content temperature should be lower than 45°C. Put not more than 2 warm containers in the stack. Put not more than 2 warm containers in the stack. When temperature decrease to 25-30° containers are characterized by optimal rigidity and mechanical parameters allowing stacking for maximal static load as below.
- Load on the lower container:
 Static (T<23°C): < 72 kg
 Transparent containers < 57 kg

- Transportation of filled containers: containers may be stacked to the 66% of maximal static load.
- Palletizing of containers: product with density 1,5 g/cm3 according to the customer practice giving consideration to the mentioned earlier values.
- All materials and dyes used to produce container or lid designed for the food sector are approved for food contact.
- This guarantee is valid 12 months from date of delivery. During this time, the package should be used. All packages from a single pallet should be used immediately after unpacking.
- Manufacturer is not responsible for container deformation because of stacking of single pallets or putting on them an extra load.

top view side view



